



TECHNICAL DATA SHEET

Date of issue: 2021

902 WATER BASED VELATURA AQUA PRIMER (EU Ecolabel: EL/044/021)

DESCRIPTION

Ecological water based substrate of premium quality, suitable for interior and exterior wooden and plastered surfaces. Certified by ASAOS according to the criteria of Eco labeling Council of EU. It offers excellent adhesion to new and previously painted surfaces. It spreads easily, ensuring excellent adhesion in the final color. Friendly to user and to environment. Ideal undercoat for waterbased enamel paints.



TECHNICAL CHARACTERISTICS

Density	: 1,25 - 1,26 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 2.500 - 3.500 mPas (ASTM D2196-86 25°C)
Resistance to wet abrasion	: 10.000 cycles(DIN 53778)
Thinning	: 5 with water for roller or brush, 10 – 20% for pistol
Coverage	: 10 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 5-6hours
Colors	: Unlimited number of shades through tinting system of TETRALUX.
Packaging	: 750ml, 2.5lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “d”, Type:WB, Interior/exterior trim and cladding paints for wood and metal: 130g/l (2010). This product contains max 79g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2021

Storage : Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances. It is applied in two layers for a perfect result. It dries in one hour and it can be recoated after 5-6 hours. Times variations may depend on weather conditions.

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. In case of residual paint, keep the container tightly closed after opening and store in dry and cool place out of reach of children. In case of unused residual paint, it is required special handling. Therefore it should not be thrown away into drains, watercourses or soil.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.