

## TECHNICAL DATA SHEET

Date of issue: 2020

### BETOCONTACT 881

#### DESCRIPTION

It is a specific resins improver of adhesion primer with quartz sand and high resistance to alkalis. It offers excellent adhesion on smooth surfaces such as architectural concrete, thermal insulation polystyrene plates, tiles etc.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,54 - 1,59 (ΕΛΟΤ EN ISO 2811 20°C)
<b>Viscosity</b>	: 6.000 - 8.500 mPas (ASTM D2196-86 25°C)
<b>pH</b>	: 8.6 – 8.9 (ASTM E70)
<b>Thinning</b>	: Without dilution
<b>Coverage</b>	: 200 – 300g/m <sup>2</sup>
<b>Drying time</b>	: Touch dry after 30 minutes and recoatable after 6-7 hours
<b>Packaging</b>	: 1kg, 5kg, 15kg
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: “g”, Type:WB, primers: 30g/l (2010). This product contains max 29g/l VOC
<b>Painting tools</b>	: Brush, roller or appropriate pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.



## TECHNICAL DATA SHEET

Date of issue: 2020

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing. • Call a POISON CENTER or doctor/physician if you feel unwell •

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations

Contains: Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

May produce an allergic reaction.

Tel. POISON CENTER: 210 7793777