



TECHNICAL DATA SHEET

Date of issue: 2021

ELITE EMULSION PAINT (interior use) (EU Ecolabel: EL/044/021)

DESCRIPTION

Ecological emulsion paint of excellent quality for interior use. The ratio of price to quality, it makes it unrivalled for putty surfaces. It is certified by ASAOS according to the criteria of Eco labeling Council of EU. It has great hiding power and high spreading rate. Also available in basic shades for coloring emulsion and acrylic paints.



TECHNICAL CHARACTERISTICS

Density	: 1,35 - 1,52 depending on the shade(EAOT EN ISO 2811 20°C)
Viscosity	: 98 - 110 KU (ASTM D562)
Resistance to wet abrasion	: >5.000cycles(DIN 53778)
Thinning	: 5-10% with water
Coverage	: 12m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Unlimited number of shades through tinting system of TETRALUX.
Packaging	: 750ml, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25 @60°): 30g/l (2010). This product contains max 9g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS&Co.L.P.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2021

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

New surfaces	1^olayer: Priming with Acrylic water based primer or water based primer TETRADUR 2^olayer: One layer of Emulsion paint Elite. Dilution 5-10% with water 3^olayer: One layer of Emulsion paint Elite. Dilution up to 5-10% with water
Painted surfaces	Scraping, puttying and priming with Acrylic water based primer or water based primer TETRADUR, if it's necessary and application of two layers of Emulsion paint Elite diluted 5-10% with water

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products lifecycle environmental impact. In case of residual paint, keep the container tightly closed after opening and store in dry and cool place out of reach of children. In case of unused residual paint, it is required special handling. Therefore it should not be thrown away into drains, water courses or soil.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.