



DIMPLE MEMBRANE 400g

STRUCTURE: it is a high density polyethylene (HDPE) studded membrane. It is ideal for protecting the waterproofing membrane in basements and underground walls. It creates an air gap between soil and wall and hinders moisture penetration

PROPERTIES

Raw material		HDPE		
Weight	EN 965	g/m ²	400	±5%
Foil thickness		mm	0,45	±0,1

PHYSICAL/ MECHANICAL CHARACTERISTICS

Thickness	-	mm	7,5	±1
Compression resistance	-	kN/m ²	>120	
Tensile strenght MD	EN ISO 10319	N/5cm	>200	
Extension at max load MD	EN ISO 10319	%	>20	
Tensile strenght CMD	EN ISO 10319	N/5cm	>200	
Extension at max load CMD	EN ISO 10319	%	>25	

DIMENSIONAL CHARACTERISTICS

STANDARD DIMENSIONS					
Roll width	m		2	2,4	±0,01
Roll lenght	m		40	30	±0,1
Roll area	m ²		80	72	
Roll weight	kg		32	28,8	±5%
Rolls/pallet	n		15	15	

Information given in this data sheet is to the best of our knowledge true and correct, however new research results and practical experience can lead up to revisions preformed without notice. No guarantee or liability can be drawn from the information mentioned herein. Furthermore, is not our intention to violate any patents or licences.



TeMa
Technologies
and Materials

TeMa Technologies and Materials srl
Via dell'Industria, 21 31029 Vittorio V.to (TV) - I -
Tel. +39.0438.50.31 - Fax +39.0438.50.34.60
e-mail: info@temacorporation.com
www.temacorporation.com

Rev. 3 gen-09